

**PRO® Eliminator™ Foam Pads** are specifically manufactured for D.A. orbital sanders & polishers and rotary high speed polishers for light compounding, polishing and final finishing. PRO® Eliminator™ Foam Pads (8 1/2") unique curved design is exceptional for safe, contour buffing in compact spaces. Another advantage is the recessed back which safeguards against accidental contact between the backing plate and the buffing surface. PRO® Mini-Eliminator™ Foam Pads (6") are designed to be used exclusively with the D.A. sander and polisher. Its flat construction allows the user maximum coverage and variable pad pressure. The fortified adhesion backing allows the quick change Velcro® loop to endure substantial friction and speed created by D.A. & rotary tools.

PRO® Eliminator™ Foam Pads are made from the most durable automotive foam materials available. Manufactured using the highest quality polyester urethane foam composite, a remarkably tough, soft and pliable material, that will not scratch. PRO® Eliminator™ Foam Pads provide professional detailers with excellent value by getting use of up to 20 vehicles from a single pad. PRO® Eliminator™ Foam Pads are safe and effective on all types of painted finishes.

PRO® Eliminator™ Foam Pads are available in three foam composites: 60ppi, 80ppi and 100ppi (ppi= pores per inch).

## 8 1/2" ELIMINATOR™ FOAM PADS

## 6" MINI ELIMINATOR™ FOAM PADS



### YW-85-C

- Firm, high density yellow polishing pad
- 60ppi
- Specially designed for light compounding and polishing
- Curved, waffle construction provides maximum coverage with superior venting
- Quick change Velcro® mount
- 8 1/2" diameter, 1 1/2" thickness
- For use with compounds & polishes
- Recommended for use at 1500-2000 rpm's

### CW-85-C

- Soft charcoal polishing pad
- 80ppi
- Specially designed for light polishing and finishing
- Curved, waffle construction provides maximum coverage with superior venting
- Quick change Velcro® mount
- 8 1/2" diameter, 1 1/2" thickness
- For use with polishes & waxes
- Recommended for use at 1200-1800 rpm's

### WW-85-C

- Super soft white final finishing pad
- 100ppi
- Specially designed for final finishing
- Curved, waffle construction provides maximum coverage with superior venting
- Quick change Velcro® mount
- 8 1/2" diameter, 1 1/2" thickness
- For use with waxes & sealants
- Recommended for use at 1200-1500 rpm's

### VF-85-C

- Firm, high density yellow polishing pad
- 60ppi
- Specially designed for light compounding and polishing
- Unique curved construction provides maximum coverage with safer buffing
- Quick change Velcro® mount
- 8 1/2" diameter, 1 1/2" thickness
- For use with compounds & polishes
- Recommended for use at 1500-2000 rpm's

### RV-85-C

- Soft charcoal polishing pad
- 80ppi
- Specially designed for light polishing and finishing
- Unique curved construction provides maximum coverage with safer buffing
- Quick change Velcro® mount
- 8 1/2" diameter, 1 1/2" thickness
- For use with polishes & waxes
- Recommended for use at 1200-1800 rpm's

### WV-85-C

- Super soft white final finishing pad
- 100ppi
- Specially designed for final finishing
- Unique curved construction provides maximum coverage with safer buffing
- Quick change Velcro® mount
- 8 1/2" diameter, 1 1/2" thickness
- For use with waxes & sealants
- Recommended for use at 1200-1500 rpm's

### YM-6-F

- Firm, high density yellow polishing pad
- 60ppi
- Specially designed for light compounding and polishing
- Flat construction provides maximum coverage and variable pad pressure
- Quick change Velcro® mount
- 6" diameter, 1 1/2" thickness
- For use with light compounds & polishes
- Recommended for use at 1500-2000 rpm's

### CM-6-F

- Soft charcoal polishing pad
- 80ppi
- Specially designed for light polishing and finishing
- Flat construction provides maximum coverage and variable pad pressure
- Quick change Velcro® mount
- 6" diameter, 1 1/2" thickness
- For use with polishes & waxes
- \* Recommended for use at 1200-1800 rpm's

### WM-6-F

- Super soft white final finishing pad
- 100ppi
- Specially designed for final finishing
- Flat construction provides maximum coverage and variable pad pressure
- Quick change Velcro® mount
- 6" diameter, 1 1/2" thickness
- For use with waxes & sealants
- Recommended for use at 1200-1500 rpm's



# ELIMINATOR™ SERIES

## FOAM PADS

- Swirl Free Results
- Produce Less Heat Than Conventional Pads
- No Lint - No Mess
- Easy To Clean
- Wobble Free Design Requires No Centering Tool
- Available In Curved Or Waffle Design
- Use With The PRO® MBP-475 or VBP-12 Backing Plate

**BAF Industries**

1910 S. Yale Steet • Santa Ana, CA

[www.prowax.com](http://www.prowax.com)